

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-299239

(43)Date of publication of application : 24.10.2000

(51)Int.Cl.

H01F 41/10
B23K 1/00
B23K 1/005
B23K 1/20

(21)Application number : 11-109354

(22)Date of filing : 16.04.1999

(71)Applicant : MATSUSHITA ELECTRIC IND CO LTD


(72)Inventor : YAMAUCHI KOSUKE
OSHIMA YUMIKO
WADA HIROSHI
OZAKI HIROMASA

(54) SOLDER JOINT METHOD FOR INSULATED WIRE AND TERMINAL

(57)Abstract:

PROBLEM TO BE SOLVED: To jointing a terminal and an insulated wire with solder uniformly and stably by winding the insulated wire around a solder-coated terminal and irradiating the wound part with a laser beam.

SOLUTION: A predetermined amount of cream solder 2 is discharged or coated onto a predetermined upper surface of a terminal 1. The solder 2 is heated with a hot plate to be temporarily melted. Thus, the surface of the solder 2 is made substantially uniform, so that the subsequent operation of winding an insulated wire 3 is facilitated. In addition, the absorbing rate of a laser beam 4 at the soldering surface is also made uniform during the irradiation of the beam 4 so that the solder joint is stabilized. Next, the wire 3 is wound around predetermined regions of a bobbin 5 and the terminal 1. Successively, the converged beam 4 is injected onto a predetermined surface of the terminal 1, whereby, while melting the solder 2 with the heat of the beam 4 and while destroying or melting the insulation sheath of the wire 3, the terminal 1 and the wound wire 3 are jointed with the solder. As a result, a uniform and stable solder joint can be obtained.



LEGAL STATUS

[Date of request for examination]

05.03.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]